

Item Number EB16518667

×

https://www.eibabo.in/gira/control-unit-1-10v-4-fold-manual-knx-222400-eb16518667

Control unit 1-10V 4-fold manual KNX 222400

Gira 222400 4010337018858 EAN/GTIN

12981,64 INR excl. VAT**

plus shipping

🔚 5-6 days* (IND)

Control unit 1-10V 4-fold manual KNX 222400 bus system KNX, mounting type REG, width in division units 4, local/manual operation, interface 1-10 V, protection class (IP) IP20, KNX control unit 1 - 10 V 4-fold with manual operation REG plus features: The control unit switches and dims electrical consumers that have a 1-10 V interface. 5 device configurations selectable. This assigns the 4 individually controllable dimming channels to the switching outputs (e.g. 4 dimming channels are assigned to a switching relay to control an RGBW light). Relay outputs that are not assigned to a dimming channel can be used as freely acting switching actuator channels. Reactions to bus voltage failure and return and after an ETS programming process can be set. Manual operation of the outputs independent of the bus with mechanical switching position indicator. Delay for actively sending feedback after bus voltage return. Logical linking function configurable for each channel. Up to three central switching functions for joint control of all dimming and switching channels. Four individually controllable dimming channels. Feedback of switching status and brightness value. Dimmable brightness range can be adjusted. Dimming behavior and dimming channels: Four individually controllable dimming channels. Feedback of switching function or forced position function can be parameterized. Time functions (on switch-off delay, staircase lighting function). With the staircase lighting function, the reaction at the end of the switch-on time can be parameterized. Inclusion of a dimming channel in up to 10 scenes possible. Burn-in function enables the commissioning of new fluorescent lamps as required by the lamp manufacturer. Switch actuator operation (optional): Independent switching outputs A2 to A4. Normally open or normally closed operation. Feedback of the switching status. Locking function or forced position in light scenes possible. Up to 10 internal scenes can be parameterized per switching output. Cyclic monitoring of the incoming switch

YOUR ADVANTAGES

Steuereinheit 1 - 10 V 4fach

) max. 100 mA

KNX°®5

10 A AC 400 V

F-6661-53610020 Line

2224 00 / 100 A1 A4 µ 16 A LO 250 V- 1



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU. *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

