



## Contactor AC/DC operation - Magnet contactor 500A 220...240VAC 3RT1076-6AP36



**Siemens**  
**3RT1076-6AP36**  
 4011209508538 EAN/GTIN

**191401,07 INR** excl. VAT\*\*  
 plus shipping

 16-17 days\* (IND)

Contactor AC/DC operation 3RT1076-6AP36 Rated control supply voltage  $U_s$  at AC 50 Hz 220 ... 240 V, Rated control supply voltage  $U_s$  at AC 60 Hz 220 ... 240 V, Rated control supply voltage  $U_s$  at DC 220 ... 240 V, type of voltage for actuation AC/DC, Rated operational current  $I_e$  at AC-1, 400 V 610A, Rated operational current  $I_e$  at AC-3, 400 V 500A, Rated operational power at AC-3, 400 V 250kW, Rated operational current  $I_e$  at AC-4, 400 V 430A, Rated operational power at AC-4, 400 V 250kW, rated operational power NEMA 294.1995kW, suitable for series installation, number of auxiliary contacts as NO 2, number of auxiliary contacts as NC 2, connection type main circuit rail connection, number of NC as main contacts 0, number of NO as main contacts 3, power contactor, AC-3 500 A, 250 kW / 400 V AC (50-60 Hz) / DC UC 220-240 V Auxiliary contacts 2 NO + 2 NC 3-pole, size S12 Busbar connections Drive: conventional screw connection Power contactor SIRIUS 3RT1 for switching n of motors. The 3RT1 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. The contactors offer the right connection to the controller for every application (directly or via PLC input). Pre-assembled auxiliary switches reduce the complexity of your setup. The 3RT1 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in various sizes and in a large power range. They can be operated with AC or DC, some variants have a wide voltage range and a PLC control input. In the main circuit, the devices can be connected via rails or box terminals. For the auxiliary and control circuits, they are also available with a spring-loaded connection for a fast, maintenance-free and vibration-proof connection. There is a wide range of accessories for these contactors, such as wiring kits that significantly reduce the wiring effort, auxiliary switches or terminal covers. Simple, efficient, always up to date - the SIRIUS modular system.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

