

Item Number EB11600192

https://www.eibabo.in/maico/fan-ventilator-for-in-house-bathrooms-er-ap-100-eb11600192



Fan - Ventilator for in-house bathrooms ER-AP 100

×

Maico ER-AP 100 0084.0170 4012799841708 EAN/GTIN

17244,86 INR excl. VAT**

plus **shipping**



16-17 days* (IND)

Fan ER-AP 100 nominal width 75mm, volume flow 100m³/h, color white, conveying medium temperature -20... 40°C, surface mounting type, rated voltage 230V, mains frequency 50Hz, configuration standard, nominal current 0.15A, speed 18501/min, material of the Plastic housing, axial direction, degree of protection (IP) other, width 236mm, height 236mm, depth 217.5mm, version with time delay switch: switch-on delay approx. 50 sec. Run-on time approx. 6 minutes. Speed cannot be controlled. Surface-mounted fan with G2 filter for ventilation of apartment kitchens, bathrooms or toilets. Easy filter change without tools. The housing can be rotated, allowing the outlet socket to be connected to the main line at the top left or top right. Color traffic white, similar to RAL 9016. Plastic outlet nozzle DN 75/80 with automatic plastic non-return flap. The extremely steep curve shows the high pressure capacity of the ER fans. All MAICO ER devices comply with protection class IP X5 and can therefore be installed in area 1 according to DIN VDE 0100-701, even with water jets. See planning information for details. Protection class II. Robust, energy-saving capacitor motor. Maintenance-free, with ball bearings closed on both sides. Electrical plug-in connection for quick assembly of the fan in the housing. General building authority approval, approval no.: Z-51.1-42. Approval notifications on request or on our homepage Volumetric flow characteristic and leakage air rate tested by TÜV Bayern eV Leakage air volume flow < 0.01 m3/h. Shaft level difference according to DIN 4109, tested by IAB Oberursel. With VDE mark.Article: ER-AP 100 VZ, design: time delay switch, delivery volume: 100 m3/h, speed: 1850 rpm, air direction: ventilation, speed controllable: no, SEC average: -6.83 kWh/(m2 a), rated voltage: 230 V, mains frequency: 50 Hz, power consumption: 29 W, IMax: 0.15 A, protection class: IP X5, mains cable: 5 / 1.5 mm2 location: wall / ceiling, type of installation: surface-mounted, system type: decentralized, material: plastic, col

YOUR ADVANTAGES



WORLDWIDE TRADECorporate video eibmarkt®



COMPLAINTS HANDLING
Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

