Item Number
EB11605285

28.03.2024/12:06

https://www.eibabo.in/maico/centrifugal-roof-fan-dn-125-roof-mounted-ventilator-325m3-h-49w-ehd-12-eb11605285



Centrifugal roof fan DN 125 - Roof mounted ventilator 325m³/h 49W EHD 12

Maico
EHD 12
0087.0301
4012799873013 EAN/GTIN

29365,73 INR excl. VAT**
plus **shipping**

16-17 days* (IND)

Centrifugal roof fan DN 125 EHD 12 Mains frequency 50Hz, rated voltage 230V, housing material sheet steel, volume flow 325m³/h, nominal power 49W, air flow temperature -20 ... 70°C, protection class (IP) IPX5, nominal width 125mm, corrosion protection galvanized, space-saving roof fan with extremely small dimensions. For venting. Elegant housing made of galvanized and powder-coated sheet steel. Aluminum cover. The cover is easily removable for cleaning work. Coated access protection grille. Centrifugal impeller with backward curved blades. Degree of protection IP X5. Motor: Outrunner condenser motor. Operating capacitor ready for connection in the terminal box. Speed controllable. Thermal overload protection as standard. Robust motor with ball bearings, maintenance-free. Installation instructions: Thanks to its low weight, no crane or goods lift is required to transport the EHD to the roof. Electrical connection: Connection to terminal block in the housing. Safety instructions: With free intake, the fan may only be put into operation if protection against accidental contact with the impeller is guaranteed in accordance with DIN EN ISO 13857. Item: EHD 12, delivery volume: 325 m3/h, impeller type: radial, speed controllable: yes, reversible: no, energy efficiency class: C, type of voltage: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, rated power: 49 W, IMax: 0 .22 A, degree of protection: IP X5, mains cable: 3 / 1.5 mm2, installation location: roof, installation position: vertical, material: sheet steel, galvanized, weight: 4.4 kg, nominal diameter: 125 mm, width: 333 mm, height : 333 mm, depth: 261 mm, conveying medium temperature at IMax: -20 °C to 70 °C, sound pressure level: 52 dB(A) / distance 3 m, free field conditions

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

COMPLAINTS HANDLING
Obliging and 100% safely

SHORT DELIVERY TIME
Warehousing

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

25 YEARS OF EXPERIENCE
In worldwide mail order

REFUND
Within 14 days

DHL TRACK & TRACE
Shipment tracking

ORDER LIVE CHAT
With order history

DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).
** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online