



**P-LED spot stainless steel IP68 12V 3.5W 3000K -  
Downlight/spot/floodlight 1x0,1...3,5W P68123502**



**EVN**  
P68123502  
4037293011693 EAN/GTIN

**7640,67 INR** excl. VAT\*\*  
plus shipping

 **16-17 days\* (IND)**

P-LED Spot eds IP68 12V 3.5W 3000K P68123502 Energy efficiency class of the supplied replaceable light source A+, Highest energy efficiency class of the replaceable light source A++, Lowest energy efficiency class of the replaceable light source E, Energy efficiency class range A++ to E, Suitable for surface mounting, Suitable for wall mounting, Suitable for Ceiling mounting, Suitable for pedestal/floor mounting, Pivoting adjustability, Lamp LED replaceable, With lamp, Suitable for number of lamps 1, Socket GZ4, Housing material Stainless steel, Surface untreated, Housing color stainless steel, Cover material Glass transparent, Type of voltage DC, Rated voltage 12 ... 12V, LED nominal current at constant current 0mA, Voltage-controlled control gear LED control gear, Without dimming function, Reflector white, Light distributor reflector, Light distribution symmetrical, Beam angle, medium beam 21-40°, Light emission direct, Degree of protection (IP) IP68, Protection class III, Appropriate et for lamp power 0.1 ... 3.5W, max. system power 3.5W, light color white, color temperature 3000 ... 3000K, color rendering index CRI 80-89, luminous flux 220 ... 220lm, rated luminous flux according to IEC 62722-2- 1 220lm, lamp luminous efficacy 68lm/W, luminous intensity 1028cd, width 0mm, height/depth 0mm, length 86mm, outer diameter 41mm, number of poles 2, conductor cross-section 0.75mm², connection type other, the solid LED spotlight can be used for a wide range of applications. Since both a tripod (mounting foot) and a ground spike are included in the scope of delivery, the spot can be mounted almost anywhere. Due to the given degree of protection, it can even be used under water up to a depth of 1.5 m. The 5m long connecting cable is equipped with a plug for the IP44 plug-in system. This means that even larger systems can be installed quickly and easily. Both the ground spike and the tripod have a fine toothed grid to prevent the spot from swiveling unintentionally. The swivel angle is 60°. If necessary, the supplied LED light source can of course be replaced at any time.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

