


**RCD B - Earth leakage circuit breaker B13/0A FS401E-B13/0.03**

**ABB**

FS401E-B13/0.03

2CCL562111E0135

7612270108558 EAN/GTIN

**7983,22 INR** excl. VAT\*\*

plus shipping



16-17 days\* (IND)

Residual current circuit breaker B FS401E-B13/0.03 number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated insulation voltage  $U_i$  500V, rated impulse withstand voltage  $U_{imp}$  4kV, rated current 13A, rated residual current 0A, residual current type A, energy limitation class 3, rated breaking capacity according to EN 61009 6kA, Rated breaking capacity according to IEC 60947-2 10kA, rated short-circuit breaking capacity  $I_{cn}$  according to EN 61009-1 10kA, instantaneous switch-off characteristic, surge current strength 0.3kA, type of voltage AC, frequency 50/60 Hz, tripping characteristic B, with locking device, overvoltage category 3, degree of pollution 2, ambient temperature during operation -25 ... 40°C, width in pitch units 1, installation depth 91mm, degree of protection (IP) IP20, connectable conductor cross-section solid 0.8 ... 35mm<sup>2</sup>, connectable conductor cross-section stranded 0.8 ... 35mm<sup>2</sup>, RCBO (RCBOs) provide personal and property protection as well as protection against electrically ignited avoid fires according to DIN VDE 0100-410 and DIN VDE 0100-530. They ensure protection of single-phase circuits against overload and short-circuit currents, protection against sinusoidal alternating currents and pulsating currents with a smooth DC residual current of up to 6 mA to earth. As well as fault protection (protection against indirect contact), additional protection (with  $I_{\Delta n} = 30$  mA) and fire protection (with  $I_{\Delta n} = 300$  mA). They meet the product standard IEC/EN 61009-1 (VDE 0664-20). Contact is made directly via the Smissline TP socket system and the outer conductor contact can be freely selected for single-phase devices (L1, L2 or L3)

**YOUR ADVANTAGES**

**WORLDWIDE TRADE**

Corporate video eibmarkt®


**99% CUSTOMER SATISFACTION**

&gt; 500,000 customers worldwide


**DHL TRACK & TRACE**

Shipment tracking


**COMPLAINTS HANDLING**

Obliging and 100% safely


**25 YEARS OF EXPERIENCE**

In worldwide mail order


**ORDER LIVE CHAT**

With order history


**SHORT DELIVERY TIME**

Warehousing


**REFUND**

Within 14 days


**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

