



**Video color front-door station V PUK 3 buttons 1-column  
- Door loudspeaker 3-button Silver AVU140...**



**TCS**  
AVU14030-0030  
4035138014540 EAN/GTIN

**104120,13 INR** excl. VAT\*\*  
plus shipping



16-17 days\* (IND)

Video color front-door station V PUK 3 buttons 1-slit AVU14030-0030, installation technology=bus system, type of installation=flush-mounted, modular design=no, with information sign=yes, number of call buttons=3, with cover=yes, protection against vandalism=yes, With camera=yes, material=stainless steel, color=other, height=252 mm, width=150 mm, depth=3 mm, video front-door station for flush mounting, AVU14030-0030 with 3 bell buttons, 1 column, stainless steel, item number: AVU14030-0030, IMAGE / VIDEO PROPERTIES, Color camera with image sensor 1/4", single-chip CMOS, diagonal angle of coverage: 130 degrees, resolution, maximum (pixel x pixel): PAL: 648 H x 488 V, resolution: 380 H TVL Color, lens 2.0 mm, F=2.5, light sensitivity: 1.0 lx (F 1.2), video output signal: (differential, coaxial) 1.1 Vp-p., device properties, video front-door station, Number of bell buttons: 3, type of installation: flush-mounted, housing type: front panel with flush-mounted box, housing material: polished stainless steel, bell button material: metal with maintenance-free contacts, shatterproof glass for nameplates, energy-saving LED nameplate lighting, opening principle: win:clip, volume of voice output: adjustable, volume of microphone sensitivity: adjustable, extended properties, light switch function: on each bell button, name/information field: white backlit, number of wires: 6- Wire required, audio, video installation mix, access to a system: possible, configuration options: manual, with service device, with configuration software, system configuration memory: interchangeably plugged in, technical data, technology: 2-wire TCS:BUS, current consumption, at rest: 140 mA, current consumption, maximum: 156 mA, front panel HxWxD mm: 252x150x3, flush-mounted box HxWxD mm: 203x126x40, camera field HxW mm: 40x72, name plate HxW mm: 19x62, information plate HxW mm: 19x62, permissible ambient temperature: -20 to +50 degrees C, UV resistance: unrestricted, recommended installation height: 1.6 m, scope of delivery, for changing name badges: win:c lip key, for labeling: nameplates, accessories, cavity wall mounting set for flush-mounted boxes: ZAU4001

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

