×



Item Number EB12601412

https://www.eibabo.in/evn/recessed-light-round-12v-gx5.3-50w-downlight-1x0...50w-620-014-eb12601412



Recessed light round 12V GX5.3 50W - Downlight 1x0...50W 620 014

60W 620 014

EVN

620 014 4037293620147 EAN/GTIN

4777,90 INR excl. VAT**

plus **shipping**



16-17 days* (IND)

Recessed luminaire round 12V GX5.3 50W 620 014, Suitable for surface mounting=no, Suitable for recessed mounting=yes, Suitable for wall mounting=no, Suitable for pendant suspension=no, Suitable for ceiling mounting=yes, Suitable for truss mounting=no, Suitable for pedestal /floor mounting=no, suitable for busbar mounting=no, suitable for clamp mounting=no, suitable for cable system=no, adjustability=rotatable and pivotable, with motion detector=no, with light sensor=no, with light source=no, suitable for number of light sources=1, Socket=GX5.3, housing material=aluminium, surface=untreated, housing color=aluminium, cover material=none, surface brushed=no, type of voltage=AC/DC, nominal voltage=12 V, with control gear=no, dimming dependent on Control gear=no, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX=no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwitch = no, manufacturer-specific dimming heno, dimming mains voltage modulation=no, dimming trailing edge=no, dimming leading edge=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Reduction=no, dimming Touch and Dim=no, dimming Zigbee=no, dimming with Push button=no, without dimming function=no, reflector=without, light emission=direct, type of protection (IP)=IP20, protection class=III, suitable for lamp power=0.1..50 W, height/depth=35 mm, outer diameter =102 mm, installation height/depth=60 mm, installation diameter=85 mm, number of poles=2, connection type=other, lamp with limited surface temperature "D mark"=no, suitable for computer workstations according to EN 12464-1=no, cover of the Luminaire with thermal insulation material possible = no, rotating and swiveling recessed ceiling light for a variety of indoor applications. Effect lighting, room lighting, accent lighting and much more can be implemented with this light. Thanks to the low-voltage socket, various light sources can be used in the light for a wide range of lighting requirements, regardless of whether it is halogen

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

