

Item Number EB10788689

×

https://www.eibabo.in/siemens/contactor-4kw-400v-18a-2no-2nc-magnet-contactor-9a-230vac-3rt2516 -1ap00-eb10788689



## Contactor 4kW/400V 18A 2NO+2NC - Magnet contactor 9A 230VAC 3RT2516-1AP00

**Siemens** 3RT2516-1AP00 4011209785090 EAN/GTIN

2693,76 INR excl. VAT\*\*

plus **shipping** 



Contactor 4kW/400V 18A 2NO+2NC 3RT2516-1AP00 Rated control supply voltage Us at AC 50 Hz 230 ... 230V, rated control supply voltage Us at AC 60 Hz 230 ... 230V, type of voltage for actuation AC, rated operational current le at AC-1, 400 V 18A , Rated operational current le at AC-3, 400 V 9A, Rated operational power at AC-3, 400 V 4kW, Rated operational current le at AC-4, 400 V 8.5A, Rated operational power at AC-4, 400 V 4kW, Suitable for series installation, number of auxiliary contacts as NO contacts 0, number of auxiliary contacts as NC contacts 0, connection type main circuit screw connection, number of NC contacts as main contacts 2, number of NC contacts as main contacts 2, power contactor, AC-3 9 A, 4 kW / 400 V 2 NO + 2 NC AC 230 V, 50/60 Hz 4-pole size S00 screw connection SIRIUS 3RT25 contactor for pole-changing in hoist motors or for switching two separate loads. The 3RT25 contactors are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. They can be combined with other components in the load feeder in a variety of ways. Many of the device combinations are tested at the factory. The contactors offer the optimal connection to the controller for every application (parallel, via ASi or IO-Link). Integrated auxiliary switches reduce the complexity of your structure. The front connections enable easy wiring. The 3RT25 contactors are climate-proof and approved worldwide (eg IEC and UL/CSA). They are available in different sizes and in a large power range with AC and DC operation. In addition to screw connection technology, the devices are also consistently available with spring-loaded connections for a fast, maintenance-free and vibration-proof connection. The comprehensive range of accessories, such as auxiliary switches, auxiliary releases, etc., is standard for all sizes. Simple, efficient, always up-to-date - the SIRIUS modular system.

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

