



Power contactor 1NC 5.5KW/400V,DC DILM12-01 (24VDC) - Magnet contactor 12A 0VAC 24VDC DILM12-01(2...



Eaton
DILM12-01(24VDC)
276880
4015082768805 EAN/GTIN

4090,79 INR excl. VAT**
plus shipping



5-6 days* (IND)

Power contactor 1NC 5.5KW/400V,DC DILM12-01(24VDC) Rated control supply voltage U_s at AC 50 Hz 0V, rated control supply voltage U_s at AC 60 Hz 0V, rated control supply voltage U_s at DC 24 ... 24V, type of voltage for actuation DC, rated operational current I_e at AC -1, 400 V 22A, rated operational current I_e at AC-3, 400 V 12A, rated operational power at AC-3, 400 V 5.5kW, rated operational current I_e at AC-4, 400 V 7A, rated operational power at AC-4, 400 V 3kW, rated operational power NEMA 7.4kW, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NC contact 1, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, application: power contactor for motors, power contactors up to 170 A, 3-pole, Utilization category: AC-1: Non-inductive or weakly inductive load, resistance furnaces, AC-3: Squirrel-cage motors: Starting, switching off during run, AC-4: Squirrel-cage motor en: Starting, counter-current braking, reversing, jogging, Connection technology: screw terminals, Note: Also suitable for motors of efficiency class IE3., IE3-capable devices are marked with the logo on the packaging., Poles: 3-pole, rated operational current AC-3 380 V 400 V: $I_e = 12$ A, rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: $I_{th} = I_e = 22$ A, encapsulated: $I_{th} = 18$ A, rated operational current AC-1 conventional thermal current 1-pole open: $I_{th} = 50$ A, encapsulated: $I_{th} = 45$ A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: $P = 3.5$ kW, 380 V 400 V: $P = 5.5$ kW, 660 V 690 V: $P = 6.5$ kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: $P = 2$ kW, 380 V 400 V: $P = 3$ kW, 660 V 690 V: $P = 4.4$ kW, Can be combined with auxiliary switch: DILA-XHI(V)..., Contact equipment NC = NC contact: 1 NC, Notes: Contact elements according to EN 50012., Integrated varistor protective circuit., With mirror contact., Current type AC/DC: direct current operation

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

