



## Contactor 75KW/400V,AC DILM150-22 (RAC240) - Magnet contactor 150A 190...240VAC 0VDC DILM150-22(R...



**Eaton**  
DILM150-22(RAC240)  
239598  
4015082395988 EAN/GTIN

**49490,73 INR** excl. VAT\*\*  
plus shipping



5-6 days\* (IND)

Power contactor 75KW/400V,AC DILM150-22(RAC240) rated control supply voltage  $U_s$  at AC 50 Hz 190 ... 240V, rated control supply voltage  $U_s$  at AC 60 Hz 190 ... 240V, rated control supply voltage  $U_s$  at DC 0V, type of voltage for actuation AC, rated operational current  $I_e$  at AC-1, 400 V 190A, rated operational current  $I_e$  at AC-3, 400 V 150A, rated operational power at AC-3, 400 V 75kW, rated operational current  $I_e$  at AC-4, 400 V 65A, rated operational power at AC-4, 400 V 33kW, Rated operational power NEMA 93kW, number of auxiliary contacts as NO contact 2, number of auxiliary contacts as NC contact 2, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, application: power contactor for motors, complete devices up to 170 A, utilization category : AC-1: Non-inductive or slightly inductive load, resistance furnaces, AC-3: Squirrel-cage motors: Starting, turning off during run, AC-4: Squirrel-cage motors re: starting, counter-current braking, reversing, jogging, connection technology: screw terminals, Note: also suitable for motors of efficiency class IE3., IE3-capable devices are marked with the logo on the packaging., Rated operational current AC-3 380 V 400 V:  $I_e$  = 150 A, rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C:  $I_{th}$  =  $I_e$  = 190 A, encapsulated:  $I_{th}$  = 144 A, rated operational current AC-1 conventional thermal current 1-pole open :  $I_{th}$  = 400 A, encapsulated:  $I_{th}$  = 360 A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V: P = 48 kW, 380 V 400 V: P = 75 kW, 660 V 690 V: P = 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P = 20 kW, 380 V 400 V: P = 33 kW, 660 V 690 V: P = 48 kW, contact configuration S = normally open: 2 NO, Contacts NC = NC: 2 NC, Notes: Switching elements according to EN 50012., Integrated protective circuit in the control electronics., With mirror contact., Type of current AC /DC: AC operation

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

