



Voltage monitoring relay 17...275V AC/DC 3UG4633-1AL30



Siemens
3UG4633-1AL30
4011209642478 EAN/GTIN

10212,60 INR excl. VAT**
plus shipping



5-6 days* (IND)

Voltage monitoring 17-275V AC/DC 1W 3UG4633-1AL30 Design of the electrical connection Screw connection, With removable terminals, 1-phase undervoltage possible, 1-phase overvoltage possible, 1-phase window possible, Includes DC voltage undervoltage function, Includes function DC voltage overvoltage, contains DC voltage window function, voltage measuring range 17 ... 275V, type of voltage of the measuring range AC/DC, rated control supply voltage Us at AC 50 Hz 17 ... 275V, rated control supply voltage Us at AC 60 Hz 17 ... 275V, rated control supply voltage Us at DC 17 ... 275V, type of voltage for actuation AC/DC, response value voltage 17 ... 275V, min. adjustable response delay time 0.1s, max. permissible response delay time 20s, min. adjustable off-delay time 0.1s, max. permissible off-delay time 20s, number of contacts as NC contact 0, number of contacts as NO contact 0, number of contacts as changeover contact 1, width 22.5mm, height 92mm, depth e 91mm, digital monitoring relay voltage monitoring, 22.5 mm from 17-275 V AC/DC exceeding and falling below self-powered interference peak delay 0.1 to 20 s hysteresis 0.1 to 150 V 1 changeover contact with or without error memory screw connection Successor product for 3UG3534, 3UG3535 Digitally adjustable voltage monitoring relay SIRIUS 3UG4 for monitoring voltages for overshoot and undershoot, eg to protect a system from damage, to protect against deep battery discharge or to switch on a system from a defined voltage. Worldwide use thanks to international certificates. The relay can be variably set to overshoot or window monitoring. Delay times and RESET behavior can be freely parameterized. Less space required in the control cabinet thanks to a narrow overall width. Reliable diagnostics by displaying the actual value and status messages. All versions with removable connection terminals. In addition to screw connection technology, the devices are also available with spring-loaded connections for a quick, maintenance-free and vibration-proof connection. The devices are divided into self-supplied and externally supplied devices, either with a wide range of voltages or with IO-Link. The comprehensive range of accessories, such as device identification labels, push-in lugs and cover caps, is the same for all relays. SIRIUS relays - a program for all cases.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

